



**SONITROL**<sup>®</sup>  
VERIFIED ELECTRONIC SECURITY



PRODUCT SUMMARY | Camera Series | **SN-3P28-OD-I**

## 3MP High-Definition IP Vandal-Dome Camera with IR

This three (3) megapixel IP vandal-dome camera with integrated IR from Sonitrol provides dual-streaming, high-definition video at a full 2048 x 1536 pixels for video surveillance applications requiring superior clarity and detail in low- or no-light situations.

The SN-3P28-OD-I is packed with all the features you might need for nearly any application including: motion detection, Digital Wide Dynamic Range for exceptional low-light/no-light day/night functionality, and compatibility with a wide variety of standardized network protocols.

The convenient and aesthetically-pleasing dome camera format allows unobtrusive and easy installation in a wide variety of areas. In addition, this camera is designed to continue functioning at top performance at temperatures as low as -30°C (-22°F) and as high as 60°C (140°F) allowing a wide range of applications.

Comes standard with a 2.8mm lens providing support for most applications. Day/Night operation allows use in varying lighting conditions down to 0 lux with IR for unrivalled nighttime video.

Dual-streaming compression permits recording at the highest quality while allowing fast live viewing from anywhere in the world regardless of available bandwidth. In addition, with full support for both variable bit rate and variable frame rate, the quality of each stream can be matched to available bandwidth for the most effective video quality possible.

When coupled with the VIGIL Series of digital video recorders and Video Management System (VMS) software from 3xLOGIC, superior point-to-point hardware compression and decompression allows for maximum performance of streamed live video providing better video quality, more concurrent streams and a lower overall hit to CPU performance.

Superior compatibility with all VIGIL products allowing the best performance and capabilities possible.



### Key Features and Benefits

Lens	2.8mm Fixed
Resolution (Megapixels)	3
H.264/MJPEG	✓
Digital Wide Dynamic Range	✓
Infrared (Low-Light, No-Light)	✓
IK10 Impact-Resistant (Vandal-Proof Camera)	✓
IP66 Weather-Resistant (Outdoor Camera)	✓
PoE (802.3 af)	✓